

## 2INDP115/2INDP116



- Easy installation
- Compact and ergonomically
- Non-reflecting safty glass



### 1U 15/17" LCD-Monitor Drawer

- 1U Drawercase 560mm deep
- RoHS conform
- Front panel lockable

### Features:

- Varions mounting slides for any 1U (19") Rack
- Integreated Teleskope-Rails
- Front panel lockable
- RGB analog LCD Display up to 1280x1024 with 300 cd/m<sup>2</sup> brightness (17")
- Non-Reflecting safty glass

### Specifications:

#### Casing:

- RoHS conform
- Heavy-duty Steel
- Casicolor RAL 7035 or RAL 9005
- Monitor open angle 0° - 105°
- Connection 1xDB-15 (VGA)



## Technical Specification LCD Monitor

Display Size:	15"	17"
Resolution:	Maximum 1024x768	Maximum 1280x1024
Number of colors::	16,2 M.	
Optical frequenz:	H: 48,4KHz – 62,5KHz V: 55,0KHz – 75,0KHz	H: 30,0KHz – 70,0KHz V: 55,0KHz – 75,0KHz
Viewing angle:	H: 120° / V: 110°	H: 140° / V: 130°
Bandwidth:	80MHz	
Brightness:	250 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
Contrast Ratio:	350:1	700:1
Response time:	8ms	
Pixel pitch:	0,297mm(H) x 0,297mm(V)	0,264mm(H) x 0,264mm(V)
Backlights:	2xCCFL	4xCCFL
Power Supply:	Input: 100V – 240V AC, 48Hz – 62HZ Output: DC 12V, 4,2A	

