

2INEM-3017RM



- Easy installation
- Compact and ergonomically
- Using worldwide possible because of
- PS/2 Connector on the front side to connect an external Mouse



1U 17" LCD-Monitor Keyboard-Drawer (2INEM-3017RM)


Features:

- Various mounting slides for any 1U (19") Rack
- integrated Teleskope-Rails
- Front panel lockable with practical knurled screws
- RGB analog LCD Display up to 1280x1024 with 300 cd/m (sq) brightness (17")

Specification:

Casing:

- RoHS conform
- Heavy-duty Steel
- Casecolor RAL 9005 (RAL 7035 on request)
- Adjustable Rack-Slides for convenient positioning of the unit when in use
- Connections 2xPS/2 (Mouse and Keyboard) and VGA
- 106 Key Windows PS/2 Keyboard with Touchpad
- Monitor open angle 0° - 105°
- Keyboard Layouts: german / us-english / french / italian and spanish (further Layouts on request)

- 
- 1U Drawercase 548mm deep
 - RoHS conform
 - Integrated Teleskope
 - PS/2 Connector in the front side to connect an external Mouse

2INEM-3017RM



Technical Specification LCD Monitor

Display Size:	17"
Resolution:	Maximum 1280x1024
Number of colors::	16,2 M.
Optical frequenz:	H: 30,0KHz – 70,0KHz V: 55,0KHz – 75,0KHz
Viewing angle:	H: 140° / V: 130°
Bandwidth:	80MHz
Brightness:	300 cd/m ²
Contrast Ratio:	700:1
Response time:	8ms
Pixel pitch:	0,264mm(H) x 0,264mm(V)
Backlights:	4xCCFL
Power Supply:	Input: 100V – 240V AC, 48Hz – 62HZ Output: DC 12V, 4,0A

