

2INS-AW1916IP



- Easy installation
- Compact and ergonomically
- 16 Port CAT.5 KVM
- Intergrated IP-Module



1U 19" LCD-Monitor Keyboard-Drawer with integrated
16 Port CAT.5 KVM and IP-Module (2INS-AW1916IP)

- 1U Drawercase **640mm** deep
- RoHS conform
- Trackball optionally
- for all Racks from 800-1000mm
- Integrated IP-Module
- 16 Port CAT.5 KVM



Features:

- Various mounting slides for any standard (800-1000mm) 1U (19") Rack
- Integrated Telescope-Rails
- Front panel lockable with practical knurled screws
- RGB analog LCD Display up to 1280x1024 with 300 cd/m² brightness (19")
- Fully integrated power supply 100V~240VAC, 50~60Hz
- 16 Port CAT.5 KVM
- Daisy-Chain without losing a Port
- Integrated IP-Module

Specifications:

Casing:

- RoHS conform
- Heavy-duty Steel
- Casecolor RAL 9005 (RAL 7035 on request)
- 106 Key Windows PS/2 Keyboard with Touchpad (Trackball optionally)
- Monitor open angle 0° - 105°
- Connection 16xRJ-45, DB-15 for Daisy Chain, RS-232
- Touchpad Keyboard Layouts: german / us-english / french / italian and spanish (further Layouts on request)



Technical Specification LCD Monitor (see 2INS- AW1916K5)

Technical Specification CAT5 KVM-Switch

Computer connections:	16 Direct
Daisy-Chain:	256 max.
Port selection:	OSD / Hot Key / Push Buttons
Connectors on the backside:	16 x RJ45 (embedded), Daisy-Chain (DB-15) , Flash-Port (RS-232)
Resolution:	Max. 1280x1024
Flash upgrade port:	RS-232
Adapter Available Distance:	300m (in connection with USB Dongles optional available)
Power Supply:	DC 12V, 4,0A
Support:	SB Connectors for PC, SUN and MAC

Technical Specification IP Module

Target Device Connection:	1xUSB mini B Type
Remote Access Connection:	1xRJ-45
Network Connection:	10/100 Ethernet, telephone line (modem needed)
Firmware Upgrade Port:	1xSerial DB9 Pin
Max. Video Resolution:	Local: 1600x1200 / Remote: 1280x1024
OS Compatibility:	MS Windows family, Unix, Sun, Solaris, Linux, Mac OSX
Browser Compatibility:	IE 6.0, Netscape 7.0, Mozilla 1.6 (or above)
IP Settings:	DHCP, Bootp, Fixed IP (DDNS supported)
Management Interface:	Web, Utility, Telnet, Serial Port
Event Log:	NFS, SMTP, SNMP trap
Housing Material:	Metal
Power Adapter:	Dual input / 5V/2,6A x 2 (Redundancy)

