

2INS-AW1916K5



- Easy installation
- Compact and ergonomically
- 16 Port CAT.5 KVM
- Retrofit IP Module



% `% Í `@ 8 !A cb]tcf`?YmVcUfX!8 fUk Yf k]h]bh[fUfYX
% `Dcfh7 5H)`?JA `fB-BG!5K % % ?)Ł

Features:

- Various mounting slides for any standard (800-1000mm) 1U (19") Rack
- Integrated Teleskope-Rails
- Front panel lockable with practical knurled screws
- RGB analog LCD Display up to 1280x1024 with 300 cd/m² brightness (19")
- Fully integrated power supply 100V~240VAC, 50~60Hz
- 16 Port CAT.5 KVM
- Daisy-Chain without losing a Port
- Retrofit IP Module

Specifications:

Casing:

- RoHS conform
- Heavy-duty Steel
- Casecolor RAL 9005 (RAL 7035 on request)
- 106 Key Windows PS/2 Keyboard with Touchpad (Trackball optionally)
- Monitor open angle 0° - 105°
- Connection 16xRJ-45, DB-15 for Daisy Chain, RS-232
- Touchpad Keyboard Layouts: german / us-english / french / italian and spanish (further Layouts on request)

- 1U Drawercase 640mm deep
- RoHS conform
- Trackball optionally
- for all Racks from 800-1000mm
- retrofit IP Module
- 16 Port CAT.5 KVM



Technical Specification LCD Monitor

Display Size:	482,6mm (19")
Resolution:	Maximum 1280x1024
Number of colors::	16,2 M.
Optical frequency:	H: 30,0KHz – 70,0KHz / V: 55,0KHz – 75,0KHz
Viewing angle:	H: 140° / V: 130°
Bandwidth:	80MHz
Brightness:	300 cd/m ²
Contrast Ratio:	700:1
Response time:	6ms
Pixel pitch:	0,294mm(H) x 0,294mm(V)
Backlights:	4xCCFL
Power Supply:	Input: 100V – 240V AC, 50Hz – 60HZ / Output: DC 12V, 4,2A

Technical Specification CAT5 KVM-Switch

Computer connections:	16 Direct
Daisy-Chain:	256 max.
Port selection:	OSD / Hot Key / Push Buttons
Connectors on the backside:	16 x RJ45 (embedded), Daisy-Chain (DB-15) , Flash-Port (RS-232)
Resolution:	Max. 1280x1024
Flash upgrade port:	RS-232
Adapter Available Distance:	300m (in connection with USB Dongles optional available)
Power Supply:	DC 12V, 4,0A
Support:	SB Connectors for PC, SUN and MAC

