

Corat-1701/1716



- Easy installation
- compact and ergonomically
- PS/2 Connector on the front side to connect an external Mouse



1U 17" LCD-Monitor Keyboard-Drawer with Dual-Rail Slides and 16 Port CAT5 KVM-Switch (Corat-1716) optionally

- 1U Drawercase
- RoHS conform
- Dual-Rail Slide
- Optional 16 Port CAT5 KVM (Corat-1716)

Features:

- Dual-Rail sliding console for any 1U (19") system rack
- Flexible External Mouse
- Monitor and Keyboard worked separately
- RGB analog LCD-Display up to 1280x1024 with 300cd/m² brightness
- Supports Microsoft Intellimouse, Logitech FirstMouse+, MouseMan+, and others
- Supports Windows , NetWare , Linux and Free BSD

Specifications:

Casing:

- RoHS conform
- Heavy-duty Steel
- Cascolor Pantone 10C Cool Gray
- Dual-Rail design has LCD-Display and Keyboard worked separately
- Adjustable Rack-Slides for convenient positioning of the unit when in use
- 106 Key PS/2 Keyboard with Touchpad
- Monitor open angle 0° - 105°
- Connection: 1xVGA / 2x PS/2 (Corat-1701), 16xRJ45 (Corat-1716)
- Keyboard Layouts: german, us-english, french, italian and spanish



Corat-1701



Corat-1716



Technical Specification LCD Monitor

Display Size:	17"
Resolution:	Maximum 1280x1024
Number of colors:	16,2 M.
Optical frequenz:	H: 30KHz – 70KHz V: 55KHz – 75KHz
Viewing angle:	H: 140° / V: 130°
Bandwidth:	80MHz
Brightness:	300 cd/m ²
Contrast Ratio:	700:1
Response time:	8ms
Pixel pitch:	0,264mm(H) x 0,264mm(V)
Backlights:	CCFL
Power Supply:	Input: 100V – 240V AC, 48Hz – 62Hz Output: DC 12V, 4,2A

Technical Specification CAT5 KVM-Switch (Corat-1716)

Computer connections:	16 Direct
Daisy-Chain:	256 max.
Port selection:	OSD / Hot Key / Push Buttons
Connectors on the backside:	16 x RJ45 (embedded), Daisy-Chain IN/OUT, Flash-Port
Resolution:	Max. 1280x1024
Flash upgrade port:	Firmware upgradeable Via Mini DIN 6 Pin console Mouse Port
Adapter Available Distance:	30m (in connection with PS/2 or USB Dongles optional available)
Power Supply:	DC 12V, 4,2A
Support:	All PS/2 Connectors are PC spezified, USB Connectors are spezified for PC, SUN and MAC

Dimension and Weight

Corat-1701	Unpacked:	584,2 x 444,5 x 44,45 mm (W x L x H)	14,1 kg
	Packing:	685,8 x 787,4 x 228,6 mm (W x L x H)	18,6 kg
Corat-1716	Unpacked:	584,2 x 444,5 x 44,45 mm (W x L x H)	15,0 kg
	Packing:	685,8 x 787,4 x 228,6 mm (W x L x H)	19,5 kg

